



UHM SERIES 4K HDR DIGITAL SIGNAGE

4K

4K UHD



OPS SLOT



16/7 USAGE



SCREEN SHARE

VESTEL

UHD displays designed to deliver your content and messaging **effortlessly**.

UHM



UHM SERIES 4K HDR DIGITAL SIGNAGE

4K

4K UHD



OPS SLOT



16/7 USAGE



SCREEN SHARE

400
NIT

400 NIT

HDR

HDR



3 x USB



4 x HDMI



MENU LOCK



PIXEL SHIFT



SCHEDULER



AUTO-LAUNCH

PANEL			
	UHM55	UHM65	UHM75
Screen Size	55"	65"	75"
Backlight Type	DLED		
Brightness (typ.)	400 cd/m ²		
Native Resolution	3840 x 2160 (UHD)		
Contrast Ratio (typ.)	1200:1	4000:1	1200:1
Dynamic Contrast	40000:1		
Panel Lifetime (min.)	30000 Hours (min.)		
Response Time (typ.)	6 ms	8 ms	
Active Area (HxV)	1210x681 mm	1428x804 mm	1650x928 mm
Viewing Angle	178 Vertical, 178 Horizontal		
Colour Value	1.07B (10 Bit)		
Screen Treatment	3H		
Haze Level	1%		
Refresh Rate	60 Hz		
Orientation	Horizontal		
Operation Hours	16/7		
Area of Usage	Indoor		
CONNECTIVITY			
	UHM55	UHM65	UHM75
RGB Input	VGA		
RGB Output	-		
Video Input	4 x HDMI, 3 x USB		
Video Output	1x HDMI		
Audio Input	Line In L/R		
Audio Output	Headphone, Optic SPDIF		
External Control	RS232, Ethernet (RJ45)		
External Sensor	RJ12		
Network	WiFi, Ethernet (RJ45)		
MECHANICAL			
	UHM55	UHM65	UHM75
Product Dimensions	1238Wx104Dx712H mm	1459Wx99Dx853H mm	1684Wx100Dx967H mm
Packaging Dimensions	1369Wx165Dx874H mm	1607Wx177Dx980H mm	1948Wx210Dx1170H mm
Product Weight	17.05 kg	24.45 kg	37.2 kg
Packaged Weight	21.65 kg	31.85 kg	50.2 kg
VESA Mounting	400x200 mm M6	400x400 mm M6	600x400 mm M6
Bezel Width	B:14 T:11 L/R: 11 mm	B:21 T:15 L/R: 15 mm	B:21 T:16 L/R: 16 mm
ENVIRONMENTAL CONDITIONS			
	UHM55	UHM65	UHM75
Operating temp.	0-40°C		
Operating Humidity	10-90%		

POWER			
	UHM55	UHM65	UHM75
Supply	110v AC - 240v AC 50/60 Hz		
Consumption (typ.)	62 W	95 W	105 W
Deep Standby		≤0.5 W	
ACCESSORY			
	UHM55	UHM65	UHM75
Standard	QSG, Power cable, Remote Control, 2 x AAA Battery		
FEATURES			
	UHM55	UHM65	UHM75
Main	Scheduler, USB Autoplay, Auto-Launch, HDMI CEC, HDMI Wakeup, Panel Lock, OSD rotation, Pixel Shift, External Control, RTC		
Mechanical	Joystick Control, IR sensor Cable, OPS module slot, Secure USB cover, Detachable Power Cable		
Speaker	2 x 10 W		

