https://www.viewsonic.com/uk/products/sheet/VG2448A-2



Key Features


- Advanced ergonomics with a 40° tilt,
- 130mm height adjustment, ±60°swivel, and ±90°pivot
- Flexible connectivity with DisplayPort,
- HDMI, VGA, and USB 3.2
- TCO & Energy Star certificated
- Versatile stand design for mounting a mini-
- PC or cloud client



Product **Description**

ViewSonic VG2448a-2 is a 24" Full HD monitor with productivity-enhancing features including IPS technology and an advanced ergonomic design for the modern-day office. Utilising SuperClear® IPS panel technology and 1080P resolution, VG2448a-2 delivers a crisp, clear image from any viewing angle. An advanced ergonomic design offers the widest range of customisable adjustments currently available to provide maximum comfort, including pivot, swivel, height adjustment, and an impressive 40° tilt, which enables you to use the monitor while standing and to have strategic group discussions around the screen. VG2448a-2 uses environmentally friendly packaging and offers a quick and easy out-of-the-box set-up via the quick release stand. The cloud client mounts on the back of the monitor stand coupled with cable management design features make VG2448a-2 perfect for deployment in cloud-based environments. Versatile connectivity options include HDMI, DisplayPort, VGA, and USB 3.2 inputs.





3/17/23, 1:03 PM

https://www.viewsonic.com/uk/products/sheet/VG2448A-2

1	https://www.vie	wsonic.com/uk/products/she	et/VG2448A-2
DISPLAY		VIDEO INPUT	
Display Size (in.):	24	Digital Sync:	TMDS - HDMI (v1.4), PCI-E -
Viewable Area (in.):	23.8		DisplayPort (v1.2)
Panel Type:	IPS Technology	Analog Sync:	Separate/Composite/SOG - RGB Analog
Resolution:	1920 x 1080	ERGONOMICS	
Resolution Type:	FHD	Height Adjust (mm):	130
Static Contrast Ratio:	1,000:1 (typ)	Swivel:	120°
Dynamic Contrast Ratio:	50M:1	Tilt (Forward/Back):	-5° / 40°
Light Source:	LED	Pivot (Right/Left):	90° / 90°
Brightness:	250 cd/m² (typ)	WEIGHT (IMPERIAL)	
Colours:	16.7M	Net (lbs):	13
Colour Space Support:	8 bit (6 bit + A-FRC)	Net Without Stand (Ibs):	7.1
Aspect Ratio:	16:9	Gross (Ibs):	18.1
Response Time (Typical GTG):	5ms	WEIGHT (METRIC)	
Response Time (GTG w/OD):	5ms	Net (kg):	5.9
Viewing Angles:	178º horizontal, 178º vertical	Net Without Stand (kg):	3.2
Backlight Life (Hours):	30000 Hrs (Min)	Gross (kg):	8.2
Curvature:	Flat	DIMENSIONS (IMPERIAL) (W)	(HXD)
		Packaging (in.):	23.4 x 15.6 x 8.3
Refresh Rate (Hz):	60	Physical (in.):	21.2 x 15.99~20.15 x 8
Blue Light Filter:	Yes	Physical Without Stand (in.):	21.2 x 12.6 x 2
Flicker-Free:	Yes	DIMENSIONS (METRIC) (WXH	
Colour Gamut:	NTSC: 72% size (Typ)sRGB: 102% size (Typ)	Packaging (mm):	595 x 396 x 210
Pixel Size:	0.275 mm (H) x 0.275 mm (V)	Physical (mm):	539 x 406.19~511.9 x 202
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical Without Stand (mm):	539 x 320 x 52
		GENERAL	000 x 020 x 02
PC Resolution (max):	1920x1080	GENERAL	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC, UkrSEPRO, UKCA
Mac® Resolution (max):	1920x1080	Regulations:	
PC Operating System:	Windows 10/11 certified; macOS tested		
Mac® Resolution (min):	1920x1080	PACKAGE CONTENTS:	VG2448A-2 x1, 3-pin Plug (IEC C13 CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB A/B Cable (v3.2
CONNECTOR			
VGA:	1		Male-Male) x1, Quick Start Guide x
USB 3.2 Type A Down Stream:	4	Recycle/Disposal:	Please dispose of in accordance wit local, state or federal laws.
USB 3.2 Type B Up Stream:	1	\//	*Warranty offered may differ from
HDMI 1.4:	1	Warranty:	market to market
	1	Power Management:	Energy Star standards
DisplayPort:			
Power in: AUDIO	3-pin Socket (IEC C14 / CEE22)		
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	12.2W		
Eco Mode (optimised):	14.13W		
,			
Consumption (typical):	16.6W		
Consumption (max):	20W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organisation:	Yes		
CONTROLS			
Physical Controls:	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Colour Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT	100 x 100 mm		
VESA Compatible:	100 x 100 mm		
	24 ~ 92647		
Frequency Horizontal:	24 ~ 82KHz		
Frequency Vertical:			

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.

50 ~ 75Hz

Frequency Vertical: