



myTeam Sharer

P/N: MTS-100SY



Laia myTeam Sharer is designed to facilitate your video conferences and presentations. It allows you to wirelessly connect various devices to your personal computer with a single click, from cameras to microphones and external speakers. All in one. It supports AirPlay and Miracast from mobile devices and its automatic wireless IP connection allows you to connect any computer. In addition, myTeam Sharer can communicate via myTeam Sharer/Dongle and myTeam Sharer/mini Dongle.

Main characteristics



BYOD wireless presentation : BYOM wireless videoconference



Simultaneous presentation of up to 4 participants



Screen sharing (Chromecast, AirPlay, etc.)



Video quality up to 4K60 via HDMI connection



myTeam Sharer Specifications: P/N: MTS-100SY

General

Windows 10/11 connections: MTS-Dongle wireless transceiver/ myTeamSharer App for Windows / Miracast / Chromecast.

macOS connections: MTS-Dongle wireless transceiver / myTeamSharer app for macOS / AirPlay / Chromecast.

Mobile device connections: Android App / AirPlay / Miracast / Chromecast

Maximum video output resolution (wireless): 1080p60 via MTS-Dongle transceiver, myTeamSharer app for Windows and macOS, plus AirPlay.

HDMI output and HDCP resolution: 1x HDMI 2.0 | 3840x2160@60/30 Hz, 1920x1080@60Hz, 1280x720@60Hz, HDCP 1.4, HDCP 2.0

Simultaneous Ethernet (RJ45)/WLAN connections: Up to 30 | Up to 16

Screen sharing: 4 + 14. Up to 4 simultaneous screens (4 main screens+14 sub-screens), adjustable layout.

Audio input: MTS-Dongle transceiver | myTeamSharer App | AirPlay | Miracast | Chromecast | USB speaker.

Audio output (analog): 1x3.5 mm jack

Wifi Band/Wideband/standard: 2.4 / 5 GHz | up to 1200 Mbit/s | IEEE 802.11b/g/n/ac

Wifi antennas: 2x2 MIMO + 1x1 MIMO (Miracast)

Security: WiFi: WPA PSK, WPA2 PSK / AES-256 bit + RSA1024 bit encrypted video transmission.

USB 2.0: (Type-C) 1x (front), (Type-A) 1x (front).

USB 3.0: (Type C) 1x (rear), 5V / 1.5 A max (max. 20 Watt via USB 3.0 connection) (Type A) 3x (rear), 5V / 1.5 A max (max. 20 Watt via USB 3.0 ports connection).

Touch-back / USB HID support : Yes, e.g. for use in conjunction with interactive displays (touch screens), whiteboards or projectors.

LAN ports: 1 x 1000 MBit/s with PoE+. RJ45 / 1x 100 MBit/s. RJ45

PoE: Standard PoE+ - IEEE802.3at

Control ports: Network: Web GUI, Telnet / RS232: 1 x 3-pin euroblock (rear).

Transceiver compatibility: MTS-101DG Dual USB-A/C dongle and MTS-102DG USB-C Touch&Play dongle

Voltage: 12V | PoE+

Consumption: max. 30 W

Dimensions and weight: 220 x 120 x 120 x 30. Including antenna: 220 x 120 x 145 x 145 | 1Kg.

Included accessories: 1 x MTS-101DG, dual USB-A/C minidongle | 1 x AC-DC adapter, 12V-3Amp, with interchangeable adapter (Euro AV, UK) | 3 x antennas | 1 x Phoenix 3 pin terminal | 2 x Wall bracket and 4 x fixing screws.